

# Aqua Mix® Non-Cement Grout Haze Remover

## 1 Product Name

Aqua Mix® Non-Cement Grout Haze Remover

## 2 Manufacturer

Custom Building Products  
 Technical Services  
 10400 Pioneer Boulevard, Unit 3  
 Santa Fe Springs, CA 90670  
 Customer Support: 800-272-8786  
 Technical Services: 800-282-8786  
 Fax: 800- 200-7765  
 Email: [contactus@cbpmail.net](mailto:contactus@cbpmail.net)  
[custombuildingproducts.com](http://custombuildingproducts.com)

## 3 Product Description

AQUA MIX NON-CEMENT GROUT HAZE REMOVER is a safe cleaner that effectively removes Single Component®, premixed, urethane, and light epoxy grout haze from the face of most common tile and natural stone products.

### Key Features

- Removes single component, urethane and light epoxy grout haze
- Non-acidic formula

### Suitable Tile Types

Natural stone (such as granite, limestone, slate and travertine), ceramic, porcelain, quarry, Saltillo.

### Limitations to the Product

- Do not allow cleaner to come in contact with any non-recommended surface
- Do not use excessive amounts of water during cleanup process as grout pigment may be washed out.
- Avoid scrubbing directly on the grout joints.
- For moderate-heavy epoxy grout haze or any epoxy grout haze cured for more than 7 days, use Aqua Mix Sealer & Coating Remover

## 4 Technical Data

### Technical Properties Chart

- Complies with all federal EPA and SCAQMD standards for VOC

### Technical Chart

Property	Test Method	Requirement	Typical Results
	pH	n/a	11-12 (alkaline)

## 5 Instructions

### Application of Product

**USE CHEMICAL-RESISTANT GLOVES, such as nitrile, when handling product.**

**DO NOT KNEEL IN THIS PRODUCT. AVOID ALL SKIN CONTACT.**

Read entire label before using.  
 Put on rubber gloves and eye protection



- Grout installations should be cured overnight at a minimum and be clean
- Sweep, vacuum, or wipe surface
- Apply solution to surface and allow to dwell for the time indicated below:

Grout Type	Time Grout has Cured		
	24 hrs	4-7 days	28+ days
Single Component, Premixed and Urethane	5-10 sec	1 min	3-5 min
Light Epoxy Haze	2-3 min	5 min	n/a

- After dwell time, agitate with a white nylon scrub brush or scrub pad.
- Clean up dirty solution. Do not allow solution to dry on surface.
- Rinse with clean water.

### Cleaning of equipment

Clean tools with water before material dries.

### Storage

- Close container tightly after each use
- Store in original container only
- Store in and use in temperatures between 45° F to 85° F (7° C to 29° C)
- Store in areas inaccessible to small children
- Do not reuse empty container, wrap and discard in trash or recycle

### Health Precautions

**CORROSIVE. CAUSES BURNS. HARMFUL IF SWALLOWED.** Wear skin and eye protection. Do not breathe vapor or spray. Contains sodium hydroxide and ethylene glycol monobutyl ether. If in eyes, flush with water for at least 15 minutes. If on skin, wash with soap and water. If respiratory tract is irritated, remove to fresh air. If irritation persists, seek medical attention. If swallowed, DO NOT induce vomiting. Seek medical attention.



# Aqua Mix® Non-Cement Grout Haze Remover

---

## 6 Availability & Cost

Location	Item Code	Size	Package
USA	010900-4	1 qt (946 ml)	Bottle
USA	010901	1 gallon (3.8 L)	Bottle
USA	010384*	5 gallon (19 L)	Pail

\* Indicates a special order item

## 7 Product Warranty

Obtain the applicable **LIMITED PRODUCT WARRANTY** at [www.custombuildingproducts.com/product-warranty](http://www.custombuildingproducts.com/product-warranty) or send a written request to Custom Building Products, Inc., Five Concourse Parkway, Atlanta, GA 30328, USA. Manufactured under the authority of Custom Building Products, Inc. © 2017 Quikrete International, Inc.

## 8 Product Maintenance

Properly applied product requires no special maintenance.

## 9 Technical Services Information

For technical assistance, contact Custom technical services at 800-282-8786 or visit [custombuildingproducts.com](http://custombuildingproducts.com).

## 10 Filing System

Additional product information is available from the manufacturer upon request.

---

### VOC Content

Maximum VOCs: 25 grams per liter

### Handling & Storage

- Close container tightly after each use
- Store in original container only
- Store in and use in temperatures between 45° F to 85° F (7.2° C to 29.4° C)
- Store in areas inaccessible to small children
- Do not reuse empty container, wrap and discard in trash or recycle

### Related Products

Aqua Mix® Cement Grout Haze Remover

