









SPECIFICATIONS: Twister 1200 2ND FILTER: HEPA (H13) optional

**VOLTAGE**: 380V 50/60Hz, 3-Phase **FILTRATION**: Automatic By Timer

**POWER:** 6.3KW (8.2HP), Ring-Blower **DUST COLLECTION**: Longopac

**RATED SPEED:** 3480 r/min **INLET:** 2" (50mm) / 3" (75mm)

**MAX. FLOW:** 680 CFM **DIMENSION:** 140 x 70 x 150 cm

MAX. PRESSURE: 47 Kpa (4800 mmAq) WEIGHT: 170 kg

**FILTER:** PTFE To Collect up to 0.3micron





## Twister-900

This single phase vacuum performs and delivers every time. With three strong motors delivering 4.7 hp, this vacuum has excellent suction and has an Auto Filter Cleaning System using a Selector Switch. This vacuum can be easily raised and lowered for transport and uses a Longopac to collect the dust. The PTFE filter collects up to 0.3 micron and an optional 2nd filter can be fitted to meet HI3 requirements. Designed for single phase and small to medium three phase floor grinders.

SPECIFICATIONS: Twister 900 2ND FILTER: PTFE (Option H13)

**VOLTAGE**: 220 V 50/60 Hz **FILTRATION**: Auto Filter Cleaning Systems By Selector Switch

POWER RATED: 3600W (1200W X 3, 4.7HP) DUST COLLECTION: Longopac

**MAX. FLOW**: 330 CFM INLET: 2" (50mm) / 3" (75mm)

**MAX. PRESSURE** 29.5 Kpa (3000mmAq) **DIMENSION**: 70 x 75 x 156 cm

**FILTER**: PTFE To Collect up to 0.3 micron **WEIGHT**: 75 kg





**SPECIFICATION**: Twister 700 **2ND FILTER**: HEPA (H13) optional

**VOLTAGE**: 220V 50/60 Hz, 1-Phase **FILTRATION**: Auto Filter Cleaning Systems By Selector Switch

**POWER:** 2400W (1200W X 2, 3.2HP) **DUST COLLECTION:** Dust Bag **RATED SPEED:** 20500 r/min **INLET:** 2" (50mm)

**MAX. FLOW:** 280 CFM **DIMENSION:** 70 x 58 x 105 cm

MAX. PRESSURE: 25.5 Kpa (2600 mmAq) WEIGHT: 54 kg

**FILTER:** PTFE To Collect up to 0.3 micron





**SPECIFICATIONS**: TWISTER 200 **2ND FILTER**: HEPA (H13) optional

**VOLTAGE**: 220V 50/60 Hz, 1-Phase **FILTRATION**: Auto Filter Cleaning Systems By Selector Switch

**POWER:** 2400W (1200W X 2, 3.2HP) **DUST COLLECTION:** Dust Bag

RATED SPEED: 20500 r/min INLET: 2" (50mm)

**MAX. FLOW:** 280 CFM **DIMENSION:** 70 x 58 x 105 cm

MAX. PRESSURE: 25.5 Kpa (2600 mmAq) WEIGHT: 54 kg

FILTER: PTFE To Collect up to 0.3micron





**SPECIFICATIONS**: Twister 100 **2ND FILTER**: PTFE (Option H13)

**VOLTAGE**: 220 V 50/60 Hz FILTRATION: Auto Filter Cleaning Systems By Selector Switch

POWER RATED: 3600W (1200W X 3, 4.7HP) DUST COLLECTION: Longopac

**SPEED**: INLET: 2" (50mm) / 3" (75mm)

**MAX. FLOW**: 330 CFM **DIMENSION**: 70 x 75 x 156 cm

**FILTER**: PTFE To Collect up to 0.3 micron **WEIGHT**: 75 kg





**SPECIFICATIONS**: Twister 50 **TANK DIAMETER**: 440mm

CAPACITY: 90L AIR FLOW RATE: 159L/S

**POWER:** 3000W **VACUUM SUCTION:** 250mbar

**VOLTAGE**: 220V-240V~ **HOSE DIAMETER**: Ø40mm

**HEIGHT**: 100cm